

Low Flow Valve

with integrated positoner

7041

SCHUBERT & SALZER
**CONTROL
SYSTEMS**

Pneumatic Control Valve for low and lowest flows with integrated positoner

- pneumatic 0,2 - 1 bar
- electro-pneumatic (also Ex-protection)
- digital, microprocessor-control

Technical Information

Nominal sizes	1/4", 1/2", 3/4" (DN 8, 15, 20)																						
Connection	NPT, BSP-thread, further connections on demande																						
Nominal Pressure	DN 8 and DN 15: PN 340 DN 20 : PN 100																						
Fluid temperature	-40°C up to +210°C Special versions -270°C up to +800°C																						
Ambient temperature	analog positoner: -10°C up to +60°C digital positoner: -10°C up to +75°C																						
Rangeability	<table> <tr> <td>Kvs</td><td>3,4 - 3,0</td><td>lin 50:1</td><td>equal% 60:1</td></tr> <tr> <td></td><td>2,15 - 0,43</td><td>lin 40:1</td><td>equal% 50:1</td></tr> <tr> <td></td><td>0,27-0,043</td><td>lin 30:1</td><td>equal% 40:1</td></tr> <tr> <td></td><td>0,026 - 0,003</td><td>lin 25:1</td><td>--</td></tr> <tr> <td></td><td>0,002 - 1,5E-6</td><td>lin 15:1</td><td>--</td></tr> </table>			Kvs	3,4 - 3,0	lin 50:1	equal% 60:1		2,15 - 0,43	lin 40:1	equal% 50:1		0,27-0,043	lin 30:1	equal% 40:1		0,026 - 0,003	lin 25:1	--		0,002 - 1,5E-6	lin 15:1	--
Kvs	3,4 - 3,0	lin 50:1	equal% 60:1																				
	2,15 - 0,43	lin 40:1	equal% 50:1																				
	0,27-0,043	lin 30:1	equal% 40:1																				
	0,026 - 0,003	lin 25:1	--																				
	0,002 - 1,5E-6	lin 15:1	--																				
Leakage rate (% of Kvs)	< 0,01 % for Kvs-value $\geq$ 0,003 (ANSI Class IV) < 0,1 % for Kvs-value $\leq$ 0,002 (ANSI Class III)																						



K_{vs}-Values

DN 8, 1/4"

0,27	0,17	0,11	0,068	0,043	0,026	0,017
0,009	0,005	0,0026	1,7E-03	1,1E-03	8,5E-04	5,1E-04
3,4E-04	2,3E-04	1,5E-04	1,0E-04	6,8E-05	4,3E-05	3,1E-05
2,1E-05	1,4E-05	8,5E-06	5,1E-06	3,4E-06	2,3E-06	1,5E-06

DN 15, 1/2"

2,15/1,88*	1,71	1,07	0,68	0,43	0,27	0,17
0,11	0,068	0,043	0,026	0,017	0,009	0,005
0,0026	1,7E-03	1,1E-03	8,5E-04	5,1E-04	3,4E-04	2,3E-04
1,5E-04	1,0E-04	6,8E-05				

DN 20, 3/4"

3,42	2,99	2,15/1,88*	1,71	1,07	0,68	0,43
0,27	0,17	0,11	0,068	0,043	0,026	0,017
0,009	0,005	0,0026				

* The stroke/flow characteristic corresponds to the characteristic of a Kvs of 2,15 up to a stroke of 75%. The real Kv-value however is only 1,88.

Materials

Body and bonnet	Stainless steel 1.4571 or 316 SST			
Actuator	Aluminium, coated			
Packing, sealing	PTFE, graphite, bellows			
Trims	for Kvs ≥ 0,0026	for Kvs ≥ 0,000014	for Kvs ≤ 0,0017	for Kvs ≥ 0,043
Plug	Stainless steel 316	Stellite	Stellite	Stainless steel 316
Seat	Stainless steel 316	Stainless steel 316, stellite	Stainless steel 416	PTFE
	Special materials on request			

По вопросам продаж и поддержки обращайтесь:
 Екатеринбург (343)384-55-89, Казань (843)206-01-48, Краснодар (861)203-40-90,
 Москва (495)268-04-70, Санкт-Петербург (812)309-46-40
 Единый адрес: ssr@nt-rt.ru
www.ssalzer.nt-rt.ru

Low Flow Valve 7041

with integrated positioner

Operating Limits

Material	Medium	Temperature °C	Δp in bar, max.	Remarks
Plug: 316 SST Seat: 316 SST	Gas	-268 up to +316	20	Trims of sizes "K" to "O" can be used for gases up to p=48 bar and t=93 °C if stellite is not possible.
		-268 up to +93	34	
	Liquids	-268 up to +316	10	
		-268 up to +93	20	
Plug: Stellite Seat: 316 SST, stellite	Gas	-268 up to +816	340	Damage due to wear or cavitation is possible.
	Liquids	-268 up to +482	206	
Plug: Stellite Seat: 416 SST (for Kvs ≤ 0,0017)	Gas	-268 up to +93	340	This standard material for the "P"-series trims is NOT recommend for hydrogen or other dry gases. In this cases a seat with a stellite inlay or a coated seat should be used.
		-29 up to +427	340	
	Liquids	-29 up to +93	68	

Selecting The Trim Guiding

Nominal Size	Trim (Order Code)	Guiding	Max. admissible pressure drop p in bar	
			Control operation	On/Off operation
DN 20, 3/4"	R - S	medium	25	40
DN 15, 1/2"	A - B	medium	35	100
DN 15, 1/2"	A - B	heavy duty	120	120
DN 15, 1/2"	C	medium	50	135
DN 15, 1/2"	C	heavy duty	200	200
DN 15, 1/2"	D - E	medium	60	275
DN 15, 1/2"	D - E	heavy duty	275	275
DN 15, 1/2"	F - J	medium	200	340
DN 15, 1/2"	F - J	heavy duty	340	340
DN 8, 1/4"	F - J	Standard	55	100
DN 8, 1/4"	F - J	medium	135	200
DN 8, 1/4"	K - O	standard	340	340
DN 8, 1/4" - DN 15, 1/2"	"P" (all)	standard	340	340

Use the table for selecting the appropriate trim guiding depending on the pressure drop for control and on/off applications. This table only refers to the guiding and does not comment any valve materials or materials of the inner parts.

Low Flow Valve 7041

with integrated positioner

Admissible Differential Pressures (NC - spring closes)

Analog positioner

DN20, 3/4" (PN100)

Kvs-value	supply air pressure [bar]	max. working pressure [bar] for spring pressure range [bar]					
		0,2 - 1,0	0,4 - 1,2	0,6 - 1,4	0,8 - 1,6	1,0 - 3,0	1,2 - 3,2
3,0 - 3,4	4,0 ±0,2	1,1	11,5	23	34,5	45,9	57,6
1,7 - 2,1	4,0 ±0,2	2	20,5	41	61,4	81,9	100
1,07	3,0 ±0,2	3,6	36,4	72,8	100	100	-
0,43 - 0,68	3,0 ±0,2	4,6	46,1	92,1	100	100	-
0,043 - 0,27	3,0 ±0,2	11,9	100	100	100	100	-
0,0026 - 0,026	3,0 ±0,2	39,5	100	100	100	100	-

DN15, 1/2" (PN340)

Kvs-value	supply air pressure [bar]	max. working pressure [bar] for spring pressure range [bar]					
		0,2 - 1,0	0,4 - 1,2	0,6 - 1,4	0,8 - 1,6	1,0 - 3,0	1,2 - 3,2
1,7 - 2,1	4,0 ±0,2	2	20,5	41	61,4	81,9	102,7
1,07	4,0 ±0,2	3,6	36,4	72,8	109,2	145,6	-
0,43 - 0,68	4,0 ±0,2	4,6	46,1	92,1	138,2	184,2	-
0,043 - 0,27	3,0 ±0,2	11,9	118,7	237,4	340	340	-
0,0026 - 0,026	3,0 ±0,2	39,5	340	340	340	340	-
0,000068 - 0,0017	3,0 ±0,2	73	-	-	-	-	-

DN08, 1/4" (PN340)

Kvs-value	supply air pressure [bar]	max. working pressure [bar] for spring pressure range [bar]					
		0,2 - 1,0	0,4 - 1,2	0,6 - 1,4	0,8 - 1,6	-	-
0,043 - 0,27	2,5 ±0,2	7,6	38,2	76,4	152,8	-	-
0,0026 - 0,026	2,5 ±0,2	25,4	127	254,1	340	-	-
0,000068 - 0,0017	2,5 ±0,2	47	235	340	-	-	-
0,0000015 - 0,000043	2,5 ±0,2	104,4	340	340	-	-	-

For P2 > 0 the admissible differential pressure may decrease significantly.
Therefore the sizing should be checked by the manufacturer.

Digital positioner

DN20, 3/4" (PN100)

Kvs-value	supply air pressure [bar]	max. working pressure [bar] for spring pressure range [bar]					
		0,2 - 1,0	0,4 - 1,2	0,6 - 1,4	0,8 - 1,6	1,0 - 3,0	1,2 - 3,2
3,0 - 3,4	3,5 - 4	11,5	23	34,5	45,9	57,4	69,1
1,7 - 2,1	3,5 - 4	20,5	41	61,4	81,9	100	100
1,07	2,5 - 4	36,4	72,8	100	100	-	-
0,43 - 0,68	2,5 - 4	46,1	92,1	100	100	-	-
0,043 - 0,27	2,5 - 4	100	100	100	100	-	-
0,0026 - 0,026	2,5 - 4	100	100	100	100	-	-

DN15, 1/2" (PN340)

Kvs-value	supply air pressure [bar]	max. working pressure [bar] for spring pressure range [bar]					
		0,2 - 1,0	0,4 - 1,2	0,6 - 1,4	0,8 - 1,6	1,0 - 3,0	1,2 - 3,2
1,7 - 2,1	3,5 - 4	20,5	41	61,4	81,9	102,4	123,1
1,07	3,5 - 4	36,4	72,8	109,2	145,6	182	-
0,43 - 0,68	3,5 - 4	46,1	92,1	138,2	184,2	230,3	-
0,043 - 0,27	2,5 - 4	118,7	237,4	340	340	-	-
0,0026 - 0,026	2,5 - 4	340	340	340	340	-	-
0,000068 - 0,0017	2,5 - 4	340	-	-	-	-	-

DN08, 1/4" (PN340)

Kvs-value	supply air pressure [bar]	max. working pressure [bar] for spring pressure range [bar]					
		0,2 - 1,0	0,4 - 1,2	0,6 - 1,4	0,8 - 1,6	-	-
0,043 - 0,27	2 - 2,5	76,4	114,6	152,8	229,3	-	-
0,0026 - 0,026	2 - 2,5	254,1	340	340	340	-	-
0,000068 - 0,0017	2 - 2,5	340	340	340	-	-	-
0,0000015 - 0,000043	2 - 2,5	340	340	340	-	-	-

For P2 > 0 the admissible differential pressure may decrease significantly.
Therefore the sizing should be checked by the manufacturer.

Low Flow Valve 7041

with integrated positioner

Admissible Diff. Pressures (NO - spring opens)

DN20, 3/4" (PN100)

Kvs-value	max. working pressure [bar]	Supply air pressure [bar] at actual working pressure P1 [bar] (admissible deviance max. +0,1 bar)			
		0 - 25	26 - 50	51 - 75	76 - Pmax
3,4	63	1,5	1,9	-	2
1,7 - 2,1	100	1,3	1,5	1,8	2
1,07	100	1,2	1,3	1,4	1,6
0,43 - 0,68	100	1,1	1,2	1,3	1,5
0,043 - 0,27	100	1,1	1,1	1,2	1,2
0,0026 - 0,026	100	1,05	1,05	1,05	1,1

DN15, 1/2" (PN340)

Kvs-value	max. working pressure [bar]	Supply air pressure [bar] at actual working pressure P1 [bar] (admissible deviance max. +0,1 bar)				
		0 - 50	51 - 100	101 - 200	201 - 300	301 - P max
1,7 - 2,1	113	1,5	2	-	-	2
1,07	164	1,3	1,6	-	-	1,8
0,43 - 0,68	210	1,2	1,5	1,9	-	1,8
0,043 - 0,27	340	1,1	1,2	1,4	1,5	1,6
0,0026 - 0,026	340	1,05	1,05	1,1	1,2	1,2
0,000068 - 0,0017	340	1,05	1,05	1,05	1,1	1,1

DN08, 1/4" (PN340)

Kvs-value	max. working pressure [bar]	Supply air pressure [bar] at actual working pressure P1 [bar] (admissible deviance max. +0,1 bar)				
		0 - 50	51 - 100	101 - 200	201 - 300	301 - P max
0,043 - 0,27	190	1,1	1,3	-	-	1,4
0,0026 - 0,026	340	1,05	1,1	1,2	1,25	1,3
0,000068 - 0,0017	340	1,05	1,05	1,1	1,2	1,2
0,0000015 - 0,000043	340	1,05	1,05	1,05	1,1	1,1


For P2 > 0 the admissible differential pressure may decrease significantly.

Therefore the sizing should be checked by the manufacturer.

The maximum supply air pressure may not be exceeded at any time !

Pressure-Temperature Table (Body)

Temperature	DN 20 (3/4")	DN 15 (1/2")	DN 8 (1/4")
°C	Adm. Pressure (bar) for stainless steel body (316, 1.4571)		
20	100	340	340
100	99	320	320
200	82	269	292
300	73	242	267
400	48	226	249
500	-	190	159



Dimensions

Nominal Size		Actuator cm²	A	B pneumatic positioner	B electropneum. positioner	B digital positioner	C
DN 8	1/4"	47	54	338	354	386	130
DN 15	1/2"	73	70	401	417	449	163
DN 20	3/4"	73	86	429	444	476	163


Dimensions in mm

Ordering Number System

[illegible]

1 - 11: Please quote all 11 sections

12: quote only if required



- Symbol: "V": Valve
- "A": Actuator (valve without body)
- "R": Repair kit (sealings)

1. Design		2. Connection		3. Body material	4. Trim	5. Positioner		6. Springs		7. Function			
Y	Low flow valve	0	Pipe thread acc. DIN 2999 / ISO	1	Stainless steel 1.4571	-	metal to metal 316 for Kvs ≥ 0,0026	6	p/p-pos. Type 8047	1	0,2 - 1 bar	-	Spring closes with positioner
		5	NPT-thread	2	Stainless steel 316 SST	0	PTFE for Kvs ≥ 0,043	7	i/p-pos. Type 8047	2	0,3 - 1,1 bar	1	Spring opens with positioner *
						1	Stellite / 316-stellited for Kvs ≥ 0,000014	8	i/p-pos. with plug conn. Type 8047	3	0,4 - 1,2 bar		(only for spring pressure range 0,2 - 1 bar)
						2	Stellite / 416 (for Kvs ≤ 0,0017)	9	i/p-pos. II 2 G Eex ib IIC T6, Type 8047	4	0,6 - 1,4 bar		
								A	digital pos. Type 8048 IPC	5	0,8 - 1,6 bar		
								C	digital pos. Type 8049 4 wire	6	1,0 - 3,0 bar		
								D	digital pos. Type 8048 IP 65	7	1,2 - 3,2 bar		
								R	digital pos. Type 8049 2 wire				
								T	digital pos. Type 8049 AS-i version				

* digital positioner 8048 only

8. Characteristic		9. Outer sealing		10. Trim guiding		11. Kvs-Value		12. Kvs-Value P-Trim (opt.)	
-	linear	-	PTFE-Packing	-	Standard	S	3,4	--	no P-Trim
1	equal percentage	1	Bellow	M	medium	R	3,0	01	0,0017
						A	2,15/1,88	02	0,0011
						B	1,7	03	0,00085
						C	1,1	04	0,00051
						D	0,68	05	0,00034
						E	0,43	06	0,00023
						F	0,27	07	0,00015
						G	0,17	08	0,00010
						H	0,11	09	6,8E-05
						I	0,068	10	4,3E-05
						J	0,043	11	3,1E-05
						K	0,026	12	2,1E-05
						L	0,017	13	1,4E-05
						M	0,0085	14	8,5E-06
						N	0,0051	15	5,1E-06
						O	0,0026	16	3,4E-06
						P	P-Trim	17	2,3E-06
		18	1.50E-06						

Ordering example: 7041/015VY02-D4---MD

Low flow valve 7041, DN 15, Pipe thread acc. DIN 2999 / ISO 228, stainless steel body 316 SST, trim 316 / 316, digital positioner, spring pressure range 0,6 - 1,4 bar, spring closes (with positioner), linear characteristics, PTFE-Packing, medium trim guiding, Kvs-value 0,68

По вопросам продаж и поддержки обращайтесь:
Екатеринбург (343)384-55-89, Казань (843)206-01-48, Краснодар (861)203-40-90,
Москва (495)268-04-70, Санкт-Петербург (812)309-46-40
Единый адрес: ssr@nt-rt.ru
www.ssalzer.nt-rt.ru